

FIND THE RIGHT HINGE

COMPARE FEATURES & BENEFITS



C2H200F



C2H300F



CH095F



CH200F



CH350



C2H100N



C2H120



CH100/300N



HDBYSC



NAUTILUS

Product	Adjustable	Gate Gap Min (in)	Gate Gap Max (in)	Total Adj (in)	Post Thickness Min (in)	Post Width Min (in)	Frame Thickness Min (in)	Frame Width Min* (in)	Rating** (lbs)
C2H200F	X	0.55	1.5	0.95	1.5	1.5	1.5	1.8	75
C2H300F	X	0.75	1.75	1	1.5	3.1	1.5	2.61	75
CH095F	X	0.7	1.9	1.2	0.875	0.985	0.875	1.02	60
CH200F	X	0.67	1.87	1.2	1.5	1.445	1.5	1.42	75
CH200FR	X	0.46	1.66	1.2	1.375***	-	1.875***	-	75
CH300F	X	0.4	1.3	0.9	1.5	2.925	1.5	2.02	75
CH300H	X	0.3	2	1	1.25	2.873	-	1.75	75
CH350F	X	0.4	1.65	1.25	1.5	3.3	1.5	2.054	150
C2H350F	X	0.75	1.71	0.96	1.5	3	1.5	2.5	135
C2H100N		0.75	0.75	-	1	1	1	1	75
C2H120NB		0.75	0.75	-	1	1.25	1	1.25	135
C2H121NB		0.375	1.22	-	-	-	0.15	1.25	135
CH090		0.75	0.75	-	0.88	0.88	0.88	0.88	60
CH100N		0.5	0.5	-	1	1	1	1	75
CH101V		-	1.25	-	-	1	-	1	75
CH102V		0.23	0.23	-	0.13	1.14	0.13	1.14	75
CH300N		0.5	0.5	-	1.25	2.87	1.25	2.87	75
NTLS-L-AA; NTLS-R-AA		1.05	1.55	0.5	0.875	1.4	0.875	1.4	125
NTLS-L-AD; NTLS-R-AD		1.05	1.55	0.5	0.875	1.4	0.875	1.4	75
HDBYSC-SWM-SWM	X	2.56	3.04	0.48	1.5	-	1.5	-	-

Point Load* (lbs)	Self-Closing	Commercial Use	Chain Link	Ornamental	Vinyl	Wood	Turn-N-Go Tensioning	Safe, Anti-Climb Design	Adjustable Closing Speeds
1500	Yes			X	X	X	X	X	X
2000	Yes				X	X	X	X	X
-	Yes			X	X				X
1000	Yes				X	X			X
-	Yes		X		X	X			X
1500	Yes				X	X			X
1200	Yes				X	X			X
1300	Yes				X	X			X
-	Yes				X	X		X	X
1500	Yes			X	X		X	X	X
1700	Yes			X	X		X	X	X
1700	Yes			X			X	X	X
900	Yes			X					X
1000	Yes			X	X				X
-	Yes			X					X
-	Yes			X					X
950	Yes				X	X			X
-	Yes			X					X
-	Yes	X	X	X					X

*Per pair **Based on a 6' H X 4' W gate ***Diameter of post